

# Safety Data Sheet

## SPIRIT 6




Safety Data Sheet dated 16/7/2014, version 3.7

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier  
Mixture identification:  
Trade name: Spirit 6  
Trade code: 12710/04
- 1.2. Relevant identified uses of the substance or mixture and uses advised against  
Recommended use:  
Degreaser detergent for mechanical parts (aerosol).
- 1.3. Details of the supplier of the safety data sheet  
Company:  
Strima Sp. z o.o.  
Swadzim, ul. Poznańska 54  
62-080 Tarnowo Podgórne  
Competent person responsible for the safety data sheet:  
mail@strima.com
- 1.4. Emergency telephone number  
Strima Sp. z o.o. +48 61 8950950

### SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture  
Directive criteria, 67/548/CE, 99/45/EC and following amendments thereof:  
Properties / Symbols:  
F+ Extremely flammable  
R Phrases:  
R12 Extremely flammable.

EC regulation criteria 1272/2008 (CLP)  
 Danger, Flam. Aerosol 1, Extremely flammable aerosol.

Adverse physicochemical, human health and environmental effects:  
No other hazards

- 2.2. Label elements  
Symbols:



- Danger  
Hazard statements:  
H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.
- Precautionary statements:  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing spray.  
P271 Use only outdoors or in a well-ventilated area.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.  
P501 Dispose of container in accordance with national regulation.
- Special Provisions:  
The manufacturer cannot be held responsible in case of damages caused by incorrect use of the product.  
Special provisions according to Annex XVII of REACH and subsequent amendments:  
Restricted to professional users.
- 2.3. Other hazards  
vPvB Substances: None - PBT Substances: None  
Other Hazards:  
No other hazards

# Safety Data Sheet

## SPIRIT 6

---

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

N.A.

#### 3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

>= 30% - < 40% Hydrocarbons, C3-4; Petroleum gas

REACH No.: 01-2119486557-22, Index number: 649-199-00-1, CAS: 68476-40-4, EC: 270-681-9

F+; R12; substance with a Community workplace exposure limit



2.5 Press. Gas H280



2.2/1 Flam. Gas 1 H220

Note K\* The substance contains < 0,1 % weight/weight 1,3-butadiene (EINECS No. 203-450-8).

>= 25% - < 30% Distillates (petroleum), hydrotreated light; Kerosine<sub>z</sub> unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presenc

REACH No.: 01-2119456620-43, CAS: 64742-47-8, EC: 926-141-6

Xn; R65-66



3.10/1 Asp. Tox. 1 H304

>= 10% - < 12.5% Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen

REACH No.: 01-2119475608-26, CAS: 64771-72-8, EC: 265-233-4

Xn; R65



3.10/1 Asp. Tox. 1 H304

>= 2.5% - < 5% Distillates (petroleum), hydrotreated light paraffinic; Baseoil ? unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the

REACH No.: 01-2119487077-29, Index number: 649-468-00-3, CAS: 64742-55-8, EC: 265-158-7

Xn; R65



3.10/1 Asp. Tox. 1 H304

Note L\* The substance contains < 3 % weight/weight DMSO extract.

>= 2.5% - < 5% 2-(2-butoxyethoxy)ethyl acetate; diethylene glycol monobutyl ether acetate

REACH No.: 01-2119475110-51, CAS: 124-17-4, EC: 204-685-9

substance with a Community workplace exposure limit

For the wording of the listed risk phrases refer to section 16.

---

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

N.A. as aerosol preparation.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

#### 4.2. Most important symptoms and effects, both acute and delayed

None

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

None

---

### SECTION 5: Firefighting measures

# Safety Data Sheet

## SPIRIT 6

- 5.1. Extinguishing media  
Suitable extinguishing media:  
CO2 or Dry chemical fire extinguisher.  
Extinguishing media which must not be used for safety reasons:  
None in particular.
- 5.2. Special hazards arising from the substance or mixture  
Do not inhale explosion and combustion gases.  
Burning produces heavy smoke.
- 5.3. Advice for firefighters  
Use suitable breathing apparatus .  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Move undamaged containers from immediate hazard area if it can be done safely.

---

### SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures  
Wear personal protection equipment.  
Remove all sources of ignition.  
Remove persons to safety.  
See protective measures under point 7 and 8.
- 6.2. Environmental precautions  
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.  
Retain contaminated washing water and dispose it.  
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.  
Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up  
Wash with plenty of water.
- 6.4. Reference to other sections  
See also section 8 and 13

---

### SECTION 7: Handling and storage

- 7.1. Precautions for safe handling  
Pressurized container. Do not perforate or burn even after use.  
Do not use near fire or other possible sources of ignition. During work phase do not smoke.
- Avoid contact with skin and eyes, inhalation of vapours and mists.  
Contaminated clothing should be changed before entering eating areas.  
Do not eat or drink while working.  
See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities  
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.  
Keep away from food, drink and feed.  
Incompatible materials:  
None in particular. See also section number 10  
Instructions as regards storage premises:  
Cool and adequately ventilated.
- 7.3. Specific end use(s)  
None in particular

---

### SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters  
Hydrocarbons, C3-4; Petroleum gas - CAS: 68476-40-4  
TLV TWA - 1000 ppm (2400mg/m3)  
TLV STEL - 4000 ppm (9600mg/m3)  
Distillates (petroleum), hydrotreated light; Kerosine<sub>2</sub> unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presenc - CAS: 64742-47-8  
TLV TWA - 1200 mg/m3  
2-(2-butoxyethoxy)ethyl acetate; diethylene glycol monobutyl ether acetate - CAS: 124-17-4  
TLV TWA - 5000 mg/m3
- DNEL Exposure Limit Values  
N.A.
- PNEC Exposure Limit Values

# Safety Data Sheet

## SPIRIT 6

N.A.

### 8.2. Exposure controls

#### Eye protection:

Wear goggles with lateral protection EN166 .

If exposure to vapours cause a sense of bother to eyes, use antigas mask with complete facial.

#### Protection for skin:

It is not necessary in case of brief contact except for wearing antistatic clean and covering garments.

In case of long and frequent contact use protective and waterproof garments to this material.

Choosing specific protection as peak, gloves, boots, overalls depends on the type of operations.

#### Protection for hands:

During normal manipulation it is not necessary a particular protection.

In case of frequent contacts protect hands with gloves resistant to solvents (OVC,PE, neoprene, not natural rubber).

#### Respiratory protection:

The levels of air concentration should be maintained under the exposure limits. If inhalation are over exposure limit use a supplied air respirator with cartridge filter. Filter type EN 141.

#### Thermal Hazards:

The aerosol container if overheated, deforms, breaks and it can be thrown a considerable distance

#### Environmental exposure controls:

Keep the container and use the product only in well ventilated place. A located ventilation may be necessary for some operations.

---

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance and colour: Pressurized container with liquefied gases

Odour: characteristic

Odour threshold: N.A.

pH: N.A.

Melting point / freezing point: N.A.

Initial boiling point and boiling range: N.A.

Solid/gas flammability: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: 2

Flash point: < 0 ° C

Evaporation rate: N.A.

Vapour pressure: 3-5 bar

Relative density: N.A.

Solubility in water: Not soluble

Solubility in oil: yes

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: > 400°C

Decomposition temperature: N.A.

Viscosity: N.A.

Explosive properties: N.A.

Oxidizing properties: N.A.

### 9.2. Other information

Miscibility: N.A.

Fat Solubility: N.A.

Conductivity: N.A.

Substance Groups relevant properties N.A.

---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable under normal conditions

### 10.2. Chemical stability

Stable under normal conditions

### 10.3. Possibility of hazardous reactions

None

# Safety Data Sheet

## SPIRIT 6

- 10.4. Conditions to avoid  
10.5. Incompatible materials  
Avoid contact with combustible materials. The product could catch fire.  
10.6. Hazardous decomposition products  
None.

---

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

Distillates (petroleum), hydrotreated light; Kerosine<sub>2</sub> unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence - CAS: 64742-47-8

a) acute toxicity:

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 5000 mg/m<sup>3</sup> - Duration: 8h

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen - CAS: 64771-72-8

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 5000 mg/m<sup>3</sup> - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

2-(2-butoxyethoxy)ethyl acetate; diethylene glycol monobutyl ether acetate - CAS: 124-17-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

---

### SECTION 12: Ecological information

#### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

It doesn't contain CHLORINE-FLUORINE-CARBIDE.

Distillates (petroleum), hydrotreated light; Kerosine<sub>2</sub> unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence - CAS: 64742-47-8

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 1000 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

Endpoint: EC50 - Species: Daphnia = 1000 mg/l - Duration h: 48 - Notes: Daphnia magna

Endpoint: EC50 - Species: Algae = 1000 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen - CAS: 64771-72-8

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 1000 mg/l - Duration h: 48

2-(2-butoxyethoxy)ethyl acetate; diethylene glycol monobutyl ether acetate - CAS: 124-17-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 10 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48

#### 12.2. Persistence and degradability

None

N.A.

#### 12.3. Bioaccumulative potential

N.A.

# Safety Data Sheet

## SPIRIT 6

- 12.4. Mobility in soil  
N.A.
- 12.5. Results of PBT and vPvB assessment  
vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects  
None

---

### SECTION 13: Disposal considerations

- 13.1. Waste treatment methods  
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force. Aerosol container can explode at temperature above 50°C if contains little gas residue. Spray all the aerosol content before disposal.  
The product has to be considered: special dangerous disposal.
- Waste disposal key:  
The aerosol as a domestic waste is excluded from the application of such a normative for industrial activity, the empty aerosol for professional use can be classified as follow: 15.01.10: packaging containing residues of dangerous substances or residues contaminated by these substances.

---

### SECTION 14: Transport information

- 14.1. UN number  
ADR-UN number: 1950  
IATA-Un number: 1950  
IMDG-Un number: 1950
- 14.2. UN proper shipping name  
ADR-Shipping Name: AEROSOLS,  
IATA-Technical name: AEROSOLS, Flammable  
IMDG-Technical name: AEROSOLS  
Limited Quantity: max 1000ml Total gross mass of package not exceed 30 kg LQ2
- 14.3. Transport hazard class(es)  
ADR-Class: 2, 5F  
ADR-Label: <UN1950 AEROSOLS>  
IATA-Class: 2.1  
IATA-Label: <UN1950 AEROSOLS>  
IMDG-Class: 2
- 14.4. Packing group
- 14.5. Environmental hazards  
Marine pollutant: No
- 14.6. Special precautions for user  
IMDG-Technical name: AEROSOLS  
Limited Quantity: max 1000ml Total gross mass of package not exceed 30 kg LQ2  
IMDG-EMS: F-D  
IMDG-MFAG: S-U
- 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code  
N.A.

---

### SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances)  
Dir. 99/45/EC (Classification, packaging and labelling of dangerous preparations)  
Dir. 98/24/EC (Risks related to chemical agents at work)  
Dir. 2000/39/EC (Occupational exposure limit values)  
Dir. 2006/8/EC  
Regulation (EC) n. 1907/2006 (REACH)  
Regulation (EC) n. 1272/2008 (CLP)  
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013  
Regulation (EU) n. 453/2010 (Annex I)  
Regulation (EU) n. 286/2011 (ATP 2 CLP)  
Regulation (EU) n. 618/2012 (ATP 3 CLP)  
Regulation (EU) n. 487/2013 (ATP 4 CLP)  
Regulation (EU) n. 944/2013 (ATP 5 CLP)

# Safety Data Sheet

## SPIRIT 6

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

None

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

15.2. Chemical safety assessment

No

---

### SECTION 16: Other information

Full text of phrases referred to in Section 3:

R12 Extremely flammable.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

H280 Contains gas under pressure; may explode if heated.

H220 Extremely flammable gas.

H304 May be fatal if swallowed and enters airways.

Classification of substances according to 1272/2008/CE (CLP-GHS) and further ATP and Regulation 790/2009/CE.

SDS drafted in accordance with 1907/2006/CE REACH and 453/2010/CE.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.